

**Water cooler**  
down to +0,5°C

# OPTIMUM



remote control box  
with 5 meters of cable

H : 990 mm  
D : 660 mm  
L : 1050 mm  
(Provide headroom + 100 mm)

## Advantages

- Water suitable for food
- Adjustment of the temperature instruction down to +0,5°C
  - Insulated tank, volume 135 litres
- Tank easy to clean with rounded angles
- Exchanger type 316 L stainless steel coil
  - Stainless steel agitator
  - Remote control box
    - Easy setting up
  - Reduced maintenance
- Integrated electrical protection



Reference	OPTIMUM 360	OPTIMUM 360 ECOLOGIC
<b>Gas</b>	R452A	R290
<b>Hourly capacity</b> Water inlet T° +20°C Water outlet T° +1°C	40 litres / hour	
<b>Hourly capacity</b> Water inlet T° +18°C Water outlet T° +3°C	50 litres / hour	
<b>Tank volume</b>	135 litres	
<b>Flowrate</b>	10 litres / min (gravitary)	
<b>Remote control box</b>	Yes	
<b>Electrical supply</b>	Voltage: 230V-1/N+E-50Hz Neutral «TT» or «TN» only	
<b>Electrical power</b>	0,78 kW/4.93A	
<b>Air condenser flowrate</b>	540 m3 / hour	
<b>Hydraulic connections</b>	Tank outlet : Threaded F/F 20-27 (3/4") Tank filling and overflow : Threaded M/M 20-27 (3/4")	
<b>Dimensions (mm)</b>	L : 1050    D : 660    H : 990 (release of +100 mm is necessary above the water cooler to remove the cover)	
<b>Dimensions of the control box (mm)</b>	L : 105    D : 95    H : 170	
<b>Weight (kg)</b>	Empty : 62 Working : 192	

## Options

- **Stainless steel wall support**

necessary to install the cooler above the dough mixer, subject to the acceptable load by walls

- **Stainless steel support to fix on wall + floor**

height to define - maxi 2 ml

- **Connection kit by flexible hose**

water filling 1,5 ml, overflow 2,5 ml and water outlet 2,5 ml with stainless steel cross

- **Water counter COMPT'O**



with manual reset,  
wiring kit and  
1/4 turn valve.

- **208V - 60Hz voltage (except UL norm)**

please, consult us for other electrical supply