


Water meter and mixer

Automatic and programmable

DMT-PROG



No contractual picture



(Dimensions with fixing device and hydraulic connections)

Advantages

- Dosage precision (volume and mix temperature)
 - High flowrate (35L/min, 60L/min, 100L/min)
 - Friendly color touch screen 7"
 - 100 programmable recipes
- Instantaneous flowing water temperature display and water volume which remaining to flow
 - Different languages, any possible dosage units
 - Possible remote pump control (dry contact)
 - Modbus communication TCP
 - Water consumption statistics and history
- Ethernet and Micro-SD port for data recovery
 - Reduced dripping

Optional

- Stainless steel box
- Stainless steel pipes and components
 - Stop by punch button
 - Dough probe
- Remote control (dry contact)
- Default report (dry contact)

Reference	DMT-PROG
Adjustment	from 0,1 to 999,9 litres
Dosage unit	0,1 litre
Operating conditions	<ul style="list-style-type: none"> • water inlet pressure : 2 bars • mini cold water temperature : 0,5°C • maxi hot water temperature : 65°C • mixed flowing water temperature (pouring water) : from 0,5 to 65°C • ambient temperature : from 2 to 50°C • electrical supply : 240V, single phase, 50 Hz / 208-230V 60 Hz
Hydraulic connections (inlet - outlet)	20-27
Accessories	<ul style="list-style-type: none"> • Water outlet flexible with cross to hang on dough mixer • Pressure reducer • Filters kit and valves for water meter inlets
Weight (in kg)	35

DMT-PROG 15-35-2V	Mixing of 2 water supplies (cold water and hot water) Electrical valves, instantaneous flowrate : 15 to 35 L/min
DMT-PROG 15-35-3V	Mixing of 3 water supplies (cold water, hot water and city water) Electrical valves, instantaneous flowrate : 15 to 35 L/min

Touch interface

